

# ARAX ONE GLOVE

PRODUCT CODE: ONECR(SIZE)



## FEATURES & BENEFITS

- Arax Knit Technology with EN388 Cut Level D Protection.
- Sand finish nitrile dip absorbs oil & grease for excellent grip in greasy conditions.
- TPR padding protects fingers & knuckles from knocks & scrapes.
- Anti-vibration foam padded palm - ideal for working with power tools.
- Anti-Static.

## APPLICATIONS

Rigging, Landscaping, Construction, Mining, Materials Handling, Demolition, Metal Fabrication, Sheet Metal Handling, Glass/Tiles/Ceramic Handling.

## PRODUCT DETAILS

**Material** : 15 Guage Seamless Arax Liner  
**Liner** : Knitted  
**Dip** : Black Nitrile Foam  
**Colour** : Hi Vis Yellow/Black  
**Sizes** : 7, 8, 9, 10, 11, 12

**Qty/Carton**  
**CHEPONECR(SIZE)** 12 pairs/120 pairs

## PHYSICAL DIMENSIONS

SIZE	PALM WIDTH	GLOVE LENGTH
7	10.0cm+/-	22.5cm+/-
8	10.2cm+/-	23.0cm+/-
9	10.5cm+/-	25.0cm+/-
10	11.3cm+/-	26.0cm+/-
11	11.5cm+/-	26.5cm+/-
12	11.7cm+/-	27.5cm+/-

## STANDARDS

### CE CATEGORY:

II Intermediary risk in accordance with:  
 EN 420 / AS / NZS2161.2:2005 General Requirements  
 EN 388:2016 Protection Against Mechanical Risks  
**Results - 4X43D**



ARAX ONE GLOVE  
 PRODUCT CODE:  
 CHEPONECR(SIZE)



AS/NZS 2161.3  
 ID No  
 BMP 668611



4X43D



## CUT TEST - ISO13997

Amount of pressure required to make an incision over a 20mm travel distance using a razor sharp blade.

PERFORMANCE LEVEL	NEWTON	WEIGHT
A	<2	200gms
B	≥5	500gms
C	≥10	1kg
D	≥15	1.5kg
E	≥22	2.2kg
F	≥30	3.0kg